



## Yuasa Technical Data Sheet

### Yuasa YBX3086 - YBX3000 SMF Batteries

#### Performance

|                          |      |
|--------------------------|------|
| Voltage                  | 12V  |
| Capacity (20-hour)       | 76Ah |
| Cold Cranking Amps (EN1) | 680A |

#### Dimensions

|        |       |
|--------|-------|
| Length | 278mm |
| Width  | 175mm |
| Height | 190mm |

#### Weights & Measures

|                       |      |
|-----------------------|------|
| Mean Weight with Acid | 19kg |
|-----------------------|------|



#### Container Features

|                           |                |
|---------------------------|----------------|
| Case Type                 | L3 DIN         |
| Cell Layout               | 1              |
| Hold Down                 | B3             |
| State of Charge Indicator | ✓              |
| Handles                   | ✓              |
| End Venting               | ✓              |
| Lid Type                  | SMF Double Lid |

#### Technology

|                         |             |
|-------------------------|-------------|
| Flame Arrestor          | ✓           |
| Technology              | Ca/Ca       |
| Separator               | PE          |
| VDA Roll Over Test      | ✓           |
| Recommended Charge Rate | 4A          |
| Performance Marking     | W3-C2-V2-E1 |


#### Terminal Type

#### Cell Assembly Layout


#### Battery Hold-down

##### T1




Standard DIN Post



Positive Terminal



Negative Terminal



Data Sheet generated on 14/12/2021 - E&OE