

Technical Data Sheet



Reaction time
works during operation



Application field
for use in all gasoline engines



Consumption
50 ml for 10 liter



Application interval
with every tank filling

Octane Booster S

Application

Add with every filling. For use in low octane fuels or engines with increased octane requirement. Sufficient for 60 L fuel. For larger capacities add 50 ml per 10 liter of fuel.

Description

GAT Octane Booster S is to increase the octane number of low octane fuels or for use in engines with higher octane requirements.

Advantages

Protects valve seats when running on unleaded fuel. Improves start and full-load performance. Provides smoother idling. Increases the octane number up to 3 points depending on fuel quality. Improved engine performance and operational reliability. Protects valve seat from excessive wear. Ensures stable combustion process and an improved CO-value.

Packing sizes	Packing Unit	Article Number
300 ml	24 x 300 ml	Art. 62037

other sizes available on request

Properties

Physical state	liquid
Color	light yellow
Density	0,88 g/cm ³ [DIN 12185]
Flashpoint	31 °C [ISO 3679]
Viscosity	0,7 mm ² /s (at 40 °C) DIN EN ISO 3104

Compatibility

Mixable with each kind of fuel/benzine/gasoline.

Safety instructions

Follow the application instructions on the technical data sheet (TDS). Read safety instructions in the Material Safety Data Sheet (MSDS) before using this product. Please keep out of reach of children. If medical advice is needed, have product container or label at hand and call poison centre/ doctor.

Disposal

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. Dispose of this product and container according to national/ regional regulations.

Although our information is based on intense product tests and studying and therefore considered as reliable, it nevertheless has solely advisory character.